



CLEAN OIL  
BRIGHT IDEAS

# A 15/25

## CJC™ Offline Filter Insert

### CJC™ Product Sheet

#### APPLICATION

The CJC™ A 15/25 Filter Insert is ideal for the fine filtration of mineral and synthetic based

- hydraulic oils
- engine lube oils
- quenching oils
- honing oils

#### FILTRATION CAPABILITY

##### • Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3  $\mu\text{m}$  absolute:**  
98.7% of all solid particles  $> 3 \mu\text{m}$
- **0.8  $\mu\text{m}$  nominal:**  
50% of all solid particles  $> 0.8 \mu\text{m}$

are retained in each pass.

The dirt holding capacity of an A 15/25 Insert is **1.5 litres** of evenly distributed solids.

##### • Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 1 kg** of degradation products.

##### • Water Removal

The water absorption potential is up to 50% (i.e. **750 mL H<sub>2</sub>O**) of the total contaminant holding capacity.

#### DIMENSIONS

The figures below are nominal:

|           |       |
|-----------|-------|
| Diameter: | 15 cm |
| Height:   | 25 cm |

#### COMPONENT

CJC™ Filter Inserts type A consist of bonded discs.  
Ingredient: Wood cellulose.

#### IDENTIFICATION

To order the A 15/25 Filter Insert, please use:

**Article No:** PA5600322



CJC™ A 15/25 Filter Insert