



CLEAN OIL
BRIGHT IDEAS

BLDA 15/25

CJC™ Offline Filter Insert

CJC™ Product Sheet

APPLICATION

The CJC™ BLDA 15/25 Filter Insert is used in CJC™ Filters ideal for filtration of

- water glycols

FILTRATION CAPABILITY

• Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3 μm absolute:**
98.7% of all solid particles $> 3 \mu\text{m}$
- **0.8 μm nominal:**
50% of all solid particles $> 0.8 \mu\text{m}$

are retained in each pass.

The dirt holding capacity of an BLDA 15/25 Insert is **1.5 litres** of evenly distributed solids.

• Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 1 kg** of degradation products.

• Water Removal

Unlike B Filter Inserts the BLDA 15/25 will not permanently hold water, as its free passage is integral to the water separation process.

DIMENSIONS

The figures below are nominal:

Diameter:	15 cm
Height:	25 cm

COMPONENT

CJC™ Filter Inserts type BLDA consist of bonded discs. Ingredient: Cotton linters (cellulose).

IDENTIFICATION

To order the BLDA 15/25 Filter Insert, please use:

Article No: PA5601333



CJC™ BLDA 15/25 Filter Insert