



CLEAN OIL
BRIGHT IDEAS

A 38/20

CJC™ Offline Filter Insert

CJC™ Product Sheet

APPLICATION

The CJC™ A 38/20 Filter Insert is ideal for the fine filtration of mineral and synthetic based

- engine lube oils
- quenching oils
- hydraulic oils
- turbine lube oils
- honing oils

FILTRATION CAPABILITY

• Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3 μm absolute:**
98.7% of all solid particles $> 3 \mu\text{m}$
- **0.8 μm nominal:**
50% of all solid particles $> 0.8 \mu\text{m}$

are retained in each pass.

The dirt holding capacity of an A 38/20 Insert is **2.5 litres** of evenly distributed solids.

• Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 4.5 kg** of degradation products.

• Water Removal

The water absorption potential is up to 50% (i.e. **1250 mL H₂O**) of the total contaminant holding capacity.

COMPONENT

CJC™ Filter Inserts type A consist of bonded discs. Ingredient: Wood cellulose.

IDENTIFICATION

To order the A 38/20 Filter Insert, please use:

Article No:

A 38/40:	PA5600301
A 38/60:	PA5600302
(A 38/80:	2 x A 38/40)
(A 38/100:	A 38/40 + A 38/60)



CJC™ A 38/20 Filter Insert