



CLEAN OIL  
BRIGHT IDEAS

# F 15/25

## CJC™ Offline Filter Insert

### CJC™ Product Sheet

#### APPLICATION

The CJC™ F 15/25 Filter Insert is used in CJC™ Filters ideal for filtration of mineral based fuels, typically:

- diesel oils
- gas oils

#### FILTRATION CAPABILITY

##### • Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3  $\mu\text{m}$  absolute:**  
98.7% of all solid particles  $> 3 \mu\text{m}$
- **0.8  $\mu\text{m}$  nominal:**  
50% of all solid particles  $> 0.8 \mu\text{m}$

are retained in each pass.

The dirt holding capacity of an F 15/25 Insert is **1.5 litres** of evenly distributed solids.

##### • Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 1 kg** of degradation products.

##### • Water Removal

The type F 15/25 Filter Insert will not permanently hold water, as its free passage is integral to the water separation process. Please look at our A- and B- Filter Inserts for water absorption abilities.

#### DIMENSIONS

The figures below are nominal:

Diameter:	15 cm
Height:	25 cm

#### COMPONENT

CJC™ Filter Inserts type F consist of bonded discs.  
Ingredient: Wood cellulose.

#### IDENTIFICATION

To order the F 15/25 Filter Insert, please use:

**Article No:** PA5600507



CJC™ F 15/25 Filter Insert